

# Leakage-Calibrator LK3P



leakage simulation

pressure measurement

easy usage

# Technical data and device information about the LK3P

## General technical data about the LK3P

- Housing: Handy and robust plastic housing
- Display: Alpha-numerical LC-Display
- Protective kind: IP 54
- Analogous Output: Analog signal of the flow sensor
- Data interface: 1 x serial RS232 for connection to e.g. a PC
- Leakage justage: By means of precision adjustment valve
- Power supply: Batteries, power supply
  
- System language: German (others on request)
- Measuring system: Massflow sensor 2/20 or 20/200 or 200/2000 Nccm/min  
Pressure sensor -100...1000 kPa
  
- Analysis method: Mass flow, relative pressure, various units adjustable
  
- Other functions: Rating according to different standards (adjustable),  
Data logging, damping function

## Device Information about the LK3P

- With the LK3P tightness inspection and leak testing equipment can be checked on correct function
- A small device with a lot of functionality
- The device is delivered with a traceable to a national standard calibration certificate
- By the selection of the different standards can be adapted to all situations occurring in the field

**A robust device that is essential for the checking and monitoring leak testing equipment.**



APT Angewandte  
Prozessorteknik GmbH  
Innungstraße 27 c  
D-50354 Hürth-Gleuel

Telefon 0 22 33 / 37 34 17  
Telefax 0 22 33 / 37 34 10  
E-Mail info@apt-huerth.de  
Internet www.apt-huerth.de