

DATA SHEET

BR-60



TECHNICAL CHARACTERISTICS

Exterior dimensions of the machine	mm	920x600x970
Interior dimensions of the vat	mm	550x400x400
Useful measurements of the work basket	mm	500x350x230
Height of the worktop	mm	970
Capacity of the vat	L	88
Power of the ultrasonic generator	W	600
Ultrasonic work frequency	kHz	28/40
Heating element	kW	2.4

ELECTRICAL CONNECTIONS

Supply voltage	V	230 - 400
Work frequency	Hz	50/60

LID

Lid opening mode	Manual
Thermal insulation	Optional

SAFETY EQUIPMENT

General switch
Security module with emergency stop
Separated Extra Low Voltage System
Thermal-acoustic insulation
Digital thermostat

STANDARD EQUIPMENT

Digital thermostat for temperature set and control
Tank drain valve 1 + 1/4"
Adjustable legs made in stainless steel and rubber
Outer panelling built in AISI 304/316. 1 mm thickness
Vat built in AISI 304/316. 2 mm thickness
Chassis built in AISI 304/316 with structural pipe
Easy to disassemble to access the equipment for maintenance

OPTIONAL EQUIPMENT

Elevator with parts grid and sway system to remove detached dirt from the parts surface
Oil Push System (OPS). Exclusive system that extends the useful life of the cleaning fluid
Auxiliary vat
Automatic lid
Tailor-made stainless steel work baskets
Automatic filling
Bath saturation control
Automatic dosing of detergent
Filtering systems. Filter press system, cloth system, sleeve system, etc.