

# AIRPURION 90



The UV-plant AIRPURION 90 with an irradiation width of 750 mm consists of a matt anodized aluminium profile with matching cover sheets.

The radiator's compartment is designed for housing a pristine-polished aluminium reflector. On its rear side the cabling as well as the electronic cut-in unit is integrated into the housing. The high UVC-intensity ensures an optimal degree of efficiency combined with a compact construction design.

applications	product line	AIRPURION 90
pharmacy	irradiation width	750 mm
medical technology	disinfection 80%	approx. 100 m <sup>3</sup>
	disinfection 88%	approx. 50 m <sup>3</sup>
laboratories	weight	3,0 kg
ripening rooms	life time of lamps	10.000 h
	dimension (L x B x H in mm)	1000 x 67 x 100
	number of lamps	1
	protection grade	IP 54
	electrical connection	110-240 50/60 Hz
	total power	90 W
	over current protection	10 A

## advantages

suitable for direct or indirect irradiation

not affecting smell or taste

low-maintenance operation

high degree of efficiency

## alternating current (VAC)

article number: 160 01500 0000

- alternating current AC
- wide voltage
- splinter protection
- dry room
- humid room

article number: 160 01600 0000

- alternating current AC
- wide voltage
- splinter protection
- dry room
- humid room

article number: 160 02400 0000

- alternating current AC
- wide voltage
- splinter protection
- dry room
- humid room

## equipment AIRPURION 90

AIRPURION wire suspension  
article number: 160 00011 0000



AIRPURION mounting rack  
article number: 160 00040 0000

PURION UV-lamp 90 W  
article number: 200 00600 0000



service-kit  
article number: 292 00900 0000

