



Your business card: The mobile orbital workstation

MOBILE ORBITAL WORKSTATION

1.2.0128



- Electrical supply integrated for auxiliary equipment: 5 x 230 V, 10 A (not suitable for the power source!)
- 2 swivel castors, Ø 160 mm, with full lock
- 2 trestle castors, Ø 280 mm
- Pull-out cylinder bracket with fixing chain above the cylinder's centre of gravity
- High-quality powder-coated finish
- Sturdy stainless steel work top, tilted
- Platform for oxygen analyser
- Fixing for bench vice with 'V' block
- Holder for open weld head
- Holder for manual hose package
- Storage space for inverter, cooling unit, etc.

Dimensions (excluding mounted brackets):

(L x W x H): 1,110 x 710 x 850 mm
Weight: unloaded approx. 70 kg



HOLDERS FOR MOBILE WORKSTATIONS

OSK C, CS AND CW HOLDER FOR MOBILE WORKSTATIONS
OSK S, SW AND G HOLDER FOR MOBILE WORKSTATIONS

1.0.5504
1.0.5503



HOLDER FOR WORK BENCH

OSK 13 S HOLDER FOR WORK BENCH
OSK C, CS AND CW HOLDER FOR WORK BENCH
OSK S, SW AND G HOLDER FOR WORK BENCH

1.3.4002
1.0.5502
1.0.5501