

EZLink™ Armless Cam & Groove

A



Application:	<ul style="list-style-type: none"> Transfer and/or unloading of fuels (petroleum or diesel) from tank truck to storage tanks Transfer of liquids compatible with the available coupling and gasket materials
Features:	<ul style="list-style-type: none"> Automatic couplers push-to-connect providing a reliable connection Low profile allows easy connection and disconnection in tight applications Coupler push tabs can be locked with safety pins and/or zip tie Compatible with standard cam & groove adaptors Lifetime warranty on stainless-steel tabs
Materials:	<ul style="list-style-type: none"> Couplings and dust caps: A356 aluminium, 316 stainless steel Coupler tabs and springs: 316 stainless steel Gasket: Buna-N
Specifications:	<ul style="list-style-type: none"> Maximum working pressure with King Crimp™ ferrules: 2" 250 PSI, 3" and 4" 150 PSI Maximum working pressure with crimp sleeves: 2" 250 PSI, 3" 125 PSI, 4" 110 PSI Maximum working pressure with band clamps: 2" 250 PSI, 3" 125 PSI, 4" 100 PSI Gasket temperature range: -15°C to 82°C



Coupler x Male NPT (Type B)		
Size (inch)	A356 Aluminium	316 Stainless Steel
	Part No.	Part No.
1½	EZL150-B-AL	EZL150-B-SS
2	EZL200-B-AL	EZL200-B-SS
3	EZL300-B-AL	EZL300-B-SS
4	EZL400-B-AL	---

BSP available upon request.



Coupler x King Crimp™ Hose Shank (Type C)		
Size (inch)	A356 Aluminium	316 Stainless Steel
	Part No.	Part No.
1½	EZL150-C-AL	EZL150-C-SS
2	EZL200-C-AL	EZL200-C-SS
3	EZL300-C-AL	EZL300-C-SS
4	EZL400-C-AL	---



Coupler x Female NPT (Type D)		
Size (inch)	A356 Aluminium	316 Stainless Steel
	Part No.	Part No.
1½	EZL150-D-AL	EZL150-D-SS
2	EZL200-D-AL	EZL200-D-SS
3	EZL300-D-AL	EZL300-D-SS
4	EZL400-D-AL	---

BSP available upon request.



Dust Caps (Type DC)		
Size (inch)	A356 Aluminium	316 Stainless Steel
	Part No.	Part No.
1½	EZL150-DC-AL	EZL150-DC-SS
2	EZL200-DC-AL	EZL200-DC-SS
3	EZL300-DC-AL	EZL300-DC-SS
4	EZL400-DC-AL	---



Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam & groove handles and gaskets, or other types of seals are not compatible and will fail.

EZLink™ Armless Cam & Groove Replacement Parts and Kits

Replacement Kits		
Size (inch)	Kit Contains	Part No.
2	2 pins, 2 springs, and 2 tabs	EZL200RPLKIT
3 and 4	2 pins, 2 springs, and 2 tabs	EZL300RPLKIT



Replacement Gaskets			
Size (inch)	Buna-N	Fluorosilicone	FKM
	Part No.	Part No.	Part No.
1½	EZL150-G-BU	EZL150-G-FV	EZL150-G-VI
2	EZL200-G-BU	EZL200-G-FV	EZL200-G-VI
3	EZL300-G-BU	EZL300-G-FV	EZL300-G-VI
4	EZL400-G-BU	EZL400-G-FV	EZL400-G-VI



Feature: • Clip is optional.

Safety Clip
Plated Carbon Steel Part No.
EZLCL400

