



SPRING LOCK WASHER VSKZ

FOR SCREWS WITH CYLINDRICAL HEAD SHAPE / REDUCED OUTER DIAMETER

size	d1	Tol.	d2 (max.)	h (mm)	s = b (mm)	Tol.	Kg/1000 pcs.
M 4	4,10	+0,3	7,00	1,70 – 2,10	1,10	+0,2	0,195
M 5	5,10		8,80	2,10 – 2,40	1,50		0,370
M 6	6,10	+0,4	9,90	2,10 – 2,40	1,50	+0,30	0,425
M 8	8,10		12,70	2,80 – 3,20	1,90		1,050
M 10	10,20	+0,6	16,10	3,70 – 4,10	2,35	+0,40	1,960
M 12	12,20	+0,8	18,30	3,70 – 4,10	2,35		2,280
M 14	14,20	+1,0	21,14	4,50 – 5,00	2,80	+0,40	3,800
M 16	16,20		24,60	5,20 – 5,90	3,30		5,940
M 20	20,20		30,60	6,40 – 7,30	4,30		12,30

Application range: special shape for screws with cylindrical head forms

Available versions: spring steel hardened 420 – 510 HV 10 with zinc flake coating or mechanical zinc plated (standard); other coatings on request.

Spring Lock Washers VSKZ are based on Deutsche Bahnnorm BN208012-T6 / Siemens-Norm SN60727