

TRASPIRANTE



BREATHABLE SUPERCOVERING WATER-PAINT FOR INTERIORS
Compliant with the directive 2004/42/CE

DESCRIPTION

Breathable water-paint for interiors, of excellent quality, thixotropic, with a non-film-forming structure, excellent covering power and whiteness, breathable and anti-mold, perfect for bathrooms, kitchens and generally rooms subject to formation of condensation.

COLOR

White.

PACKAGING

Lt. 4 – 14 Plastic containers.

COMPOSITION

Based on copolymer resins in aqueous dispersion, selected aggregates, inorganic pigments inalterable over time and additives tested to improve the workability.



USE

For the internal paint of surfaces both old and new as float plasters based on gypsum and on cement, walls skim coated with stucco, plasterboard, wallpapers, wood and generally non-ferrous substrates. Perfect for re-painting.

TECHNICAL SPECIFICATIONS

Specific Weight $\pm 5\%$ UNI EN ISO 2811-1	1,700 Kg/lit
Dry residue UNI EN ISO 3251	71%
PH	$\geq 8,5$
Viscosity	$\sim 55.000\text{mPa}\cdot\text{s}$
Minimum Temp. for the film formation	$+5^\circ\text{C}$
Theoric yield	8/10 mq/lit for each coat
Limit value UE of the content of VOC (2010)	$\leq 30\text{ gr/lit}$
Content of VOC	$\leq 12\text{ gr/lit}$
Classification DIRECTIVE 2004/42/CE	A/BA

APPLICATION

- Prepare the substrates, both old and new, making sure that are perfectly dried and clean, removing all the crumbling and inconsistent parts and dusts, mud, bitumen, oil stains, etc.
- Brush carefully any old paints not adherent to the substrate.
- Make sure that the substrates are free of saline efflorescence and stains of active humidity.
- Make a first layer of preparation of the ground with an insulating primer ad with an high penetration "PREVIT" diluted with clean water up to a ratio of 1:5 depending on the absorption of the substrate.
- Make then a partial plastering or a complete skim coating after 6/12 hours at least with "MALVISTUK" paste stucco or "MICRORAS SB" powder stucco for interiors.
- Then apply a coat of primer "PREVIT" " to uniform the absorption diluted with clean water up to a ratio of 1:5 depending on the absorption of the substrate.
- Then apply a first coat of product diluted at 40/45% in volume with clean water.
- Then apply a second coat of product diluted at 30/35% in volume with clean water.
- Apply with a roller on the same way.
- Waiting time between the first and the second coat 6 hour at least.

TRASPIRANTE



- Don't apply on frozen substrates, with frost or possible frost in 24 hours.
- Don't apply with strong wind.
- Don't apply until when the substrate hasn't completely dried.
- Don't apply on exteriors.
- We suggest to apply TRASPIRANTE with a temperature between + 5 ° C and + 30 ° C.

FILM FEATURES

Matt, good resistance, excellent adhesion, breathable, anti-mold, antibacterial.

DILUTION

From 30 to 45% in volume with clean water; with a roller ready to use.

USE

Brush, spray and roller.

DRYING TIME

About 4 hours to the touch.

COMPATIBILITY

With every product based on resins in aqueous dispersion.

SUMMARY

The internal protection and the decoration will be realized with a breathable water paint for interiors based on resins in aqueous dispersions, type "TRASPIRANTE" by MALVIN S.r.l., applied in two coats with a brush or by spray dilution from 30 to 45% in volume with clean water; with a roller ready to use, with a yield of 8/10 mq/lt for each coat, on surfaces previously treated with primer "PREVIT".

MALVIN

The performance characteristics refer to laboratory tests, values depend on the weather conditions and on the method of implementation. The user must verify that the product is suitable for the intended application.



MALVIN



SEDE LEGALE E STABILIMENTO • Zona ASI - SS 7 Bis Km 15,400 - 81030 Gricignano di Aversa (CE)
TEL. + 39 081 8132780 - 5029713 • Numero Verde 800 - 142 999 • FAX + 39 081 5029748 • commerciale@malvinsrl.com - www.malvinsrl.com