

MXR 0,4/1,4-PVC

Product-Nr.: 1200



Usage

Low-noise coaxial measuring cables are used wherever the smallest voltages or charges have to be reliably measured, e.g. in pH measurement technology or nuclear research. The method was developed by bda connectivity and ensures reproducible results. Depending on the requirements, these cables can be supplemented with supply or power supply wires as well as additional shields.

Mechanical Properties

Min. bending radius (dynamic) [mm]	30
Min. bending radius (static) [mm]	15
Max. tensile strenght [N]	40
Operating temperature range [°C]	-20 / +70
UV-resistance	Very good

Construction

Photo	Colours and design may differ from the picture
Inner conductor dimensions [mm]	0,40
Inner Conductor material	Cu bare
Insulation dimensions [mm]	1,40
Insulation material	PE
Conudctive layer material	semi-conductive PVC
Conductive layer dimensions [mm]	1,90
1. Outer Conductor dimensions [mm]	2,15
1. Outer Conductor material	Cu braid
1. Outer Conductor opt. coverage [%]	91
Jacket material	PVC grey
Jacket dimensions [mm]	2,90 ± 0,10
Construction Number	900690

Electrical Properties

Characteristic impedance [Ω]	50
Capacitance approx. [pF/m]	102
Velocity ratio [v/c]	0,66
DC resistance inner conductor [Ω/km]	<150
DC resistance outer conductor [Ω/km]	<35
Insulation resistance [M Ohm * km]	>100
Noise voltage [mV]	<5
Max. current carrying capacity [A]	1,5

Alle Angaben verstehen sich, falls nicht anders angegeben, als Nennwert. Änderungen in Konstruktion und Ausführung vorbehalten. Entwicklung Kabel - Judt - 05026701 - 2011-03-11.