

# AIRPURION 48



The UV-plant AIRPURION 48 with an irradiation width of 380 mm consists of a matt anodized aluminium profile with matching cover sheets.

The radiator's compartment is designed for housing a pristine-polished aluminium reflector. On its rear side the cabling as well as the electronic cut-in unit is integrated into the housing. The high UVC-intensity ensures an optimal degree of efficiency combined with a compact construction design.

applications	product line	AIRPURION 48
pharmacy	irradiation width	380 mm
medical technology	disinfection 80%	approx. 70 m <sup>3</sup>
	disinfection 88%	approx. 35 m <sup>3</sup>
laboratories	weight	2,0 kg
ripening rooms	life time of lamps	10.000 h
	dimension (L x B x H in mm)	700 x 67 x 100
	number of lamps	1
	protection grade	IP 54
	electrical connection	110-240 50/60 Hz
	total power	48 W
	over current protection	10 A

## advantages

suitable for direct or indirect irradiation

not affecting smell or taste

low-maintenance operation

high degree of efficiency

## alternating current (VAC)



article number: 160 01300 0000

alternating current AC  
wide voltage  
splinter protection  
dry room  
humid room

• | • | • | • | •



article number: 160 01400 0000

alternating current AC  
wide voltage  
splinter protection  
dry room  
humid room

article number: 160 03200 0000

• | • | • | • | •

## equipment AIRPURION 48

AIRPURION wire suspension  
article number: 160 00011 0000



AIRPURION mounting rack  
article number: 160 00040 0000

PURION UV-lamp 48 W  
article number: 200 00500 0000



service-kit  
article number: 292 00900 0000

