


## Metallic Hose



Technical Characteristics	
<b>Application</b>	Versatile robust hose suited to high pressure, high temperature and corrosive applications, flexible metal hoses can accommodate angular movements, temperature expansion, vibration and misalignment. Dixon offers a variety of metallic hose options suited to individual applications including steam, compressed air, petrochemical and vacuum
<b>Description</b>	Corrugated flexible metal hose assembly meeting the requirements of class 1 of the EN ISO 10380 standard
<b>Hose Material</b>	AISI 316L or AISI 321 stainless steel & exotics
<b>Braid Material</b>	AISI 304
<b>Bore Size Range</b>	6mm to 300mm
<b>Temperature Range</b>	-200°C to 650°C
<b>Available Options</b>	<ul style="list-style-type: none"> <li>• Convoluted Core Only</li> <li>• Single, Double or Triple Braid</li> <li>• HP &amp; THP High Pressure</li> <li>• A range of standard and close pitch constructions</li> <li>• Radiograph, NDT or Dyepen</li> </ul>

Adflex Commercial Grade Metallic Hose						
Nominal I.D	Maximum O.D (mm)		Dynamic Bend Radius (mm)	Static Bend Radius (mm)	Max Working Pressure (Bar)	
	Without Braid	With Braid			No Braid	Single Braid
DN 6	12.2	13.4	100	25	4	100
DN 10	15.8	17.0	150	40	4	90
DN 12	17.5	18.7	200	50	3	80
DN 15	22	23.2	200	50	2	64
DN 20	26.3	27.5	200	70	2	64
DN 25	33.8	35.3	200	90	2.0	50
DN 32	42	43.6	250	110	1.5	40
DN 40	51.6	53.2	250	130	1.5	30
DN 50	61.7	63.3	350	175	1.0	28
DN 65	77	79.0	410	200	1.0	24
DN 80	91	93.0	450	205	1.0	18
DN 100	117.5	119.5	560	230	0.8	16
DN 125	149	151	660	280	0.6	12
DN 150	178	180	815	320	0.6	10
DN 200	228	230.4	1015	435	0.5	8
DN 250	278	280.4	1220	560	0.5	6
DN 300	333	335.8	1420	660	0.3	5
DN 300	336	339	1525	725	0.1	6

Note: Dimension tolerances meeting the requirements of class 1 of the EN ISO 10380 standard applies. De-rating factors will apply for elevated temperature applications, refer to the technical section or call Dixon for further information.

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice

## Metallic Hose (continued)

Suparflex Standard Pitch Metallic Hose												
Nominal I.D	Maximum O.D (mm)			Dynamic Bend Radius (mm)			Static Bend Radius (mm)			Max Working Pressure (Bar)		
	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid
DN 6	9.8	11.4	13	-	110	140	10	23	25	18	140	145
DN 8	13.6	15.2	16.8	-	130	130	14	28	32	14	115	121
DN 10	16.2	17.8	19.4	-	150	150	16	32	38	10	90	105
DN 12	18.6	17.8	19.4	-	165	165	24	39	45	12	80	97
DN 15	22.5	24.1	25.7	-	195	195	29	50	58	7.5	63	77
DN 20	28.3	29.9	31.5	-	225	225	35	60	70	4.3	50	68
DN 25	34.8	36.4	38	-	260	260	42	73	85	3	40	55
DN 32	43.3	45.4	47.4	-	300	300	51	90	105	3.3	40	55
DN 40	52.4	54.4	56.4	-	340	340	61	115	130	2.2	32	44
DN 50	64.8	67.3	69.8	-	390	390	73	140	160	2.1	32	45
DN 65	80.9	83.4	85.9	-	460	460	89	175	200	1.3	25	38
DN 80	99.6	102.6	105.6	-	660	660	108	240	240	1.4	23	38
DN 100	126.5	129.5	132.5	-	750	750	126	290	290	0.5	15	25
DN 125	152	155	-	-	1000	-	147	340	-	0.4	13	-
DN 150	174	177	-	-	1250	-	169	390	-	0.3	11	-

Note: Dimension tolerances meeting the requirements of class 1 of the EN ISO 10380 standard applies. De-rating factors will apply for elevated temperature applications, refer to the technical section or call Dixon for further information.

Hyparflex Close Pitch Metallic Hose												
Nominal I.D	Maximum O.D (mm)			Dynamic Bend Radius (mm)			Static Bend Radius (mm)			Max Working Pressure (Bar)		
	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid	No Braid	Single Braid	Double Braid
DN 6	9.8	11.4	13	-	110	140	9	20	25	18	150	175
DN 8	13.6	15.2	16.8	-	130	130	12	20	32	9	115	158
DN 10	16.2	17.8	19.4	-	150	150	14	20	38	6	115	135
DN 12	18.6	20.2	21.8	-	124	124	21	25	45	6	80	125
DN 15	22.5	24.1	25.7	-	164	164	26	32	58	3	63	97
DN 20	28.3	29.9	31.5	-	169	169	32	38	70	2.2	55	77
DN 25	34.8	36.4	38	-	195	195	37	45	85	1.8	40	62
DN 32	43.4	45.4	47.4	-	225	225	46	58	105	1.6	40	58
DN 40	52.4	54.4	56.4	-	255	255	55	70	113	1.2	32	44
DN 50	64.8	67.3	69.8	-	293	293	65	85	136	1	32	47
DN 65	80.9	83.4	85.9	-	345	345	80	105	171	0.5	25	41
DN 80	99.6	102.6	105.6	-	495	495	97	180	224	0.7	23	40
DN 100	126.5	129.5	132.5	-	563	563	113	218	276	0.4	15	27
DN 125	152	155	-	-	1000	-	132	255	-	0.25	13	-
DN 150	174	177	-	-	1250	-	152	290	-	0.2	11	-

Note: Dimension tolerances meeting the requirements of class 1 of the EN ISO 10380 standard applies. De-rating factors will apply for elevated temperature applications, refer to the technical section or call Dixon for further information.

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice

HP/THP High Pressure Metallic Hose						
Nominal I.D	Maximum O.d (Mm)		Dynamic Bend Radius (mm)	Static Bend Radius (mm)	Max Working Pressure (Bar)	
	Single Braid	Double Braid			Single Braid	Double Braid
DN 6	11.4	13	110	25	180	255
DN 10	17.8	19.4	150	38	145	195
DN 12	20.2	21.8	165	45	140	185
DN 20	29.1	30.7	225	70	85	125
DN 25	38	40	215/ 260	85	78	124
DN 32	46.5	49	300	105	65	115
DN 40	54.9	57.4	280/ 340	130	61	90
DN 50	67.3	69.8	390	160	55	78
DN 65	83.9	86.9	460	200	52	75
DN 80	99	102	660	240	25	50
DN 100	129.5	132.5	750	290	24	45
DN 125	155	158	1000	350	20	38
DN 150	185	188	1250/ 1550	400	27	34
DN 200	246	253.5	1600/ 2000	520	27	30

Note: Dimension tolerances meeting the requirements of class 1 of the EN ISO 10380 standard applies. De-rating factors will apply for elevated temperature applications, refer to the technical section or call Dixon for further information.

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice




Telephone: +44 (0)1772 323529

Email: [sales@dixoneurope.co.uk](mailto:sales@dixoneurope.co.uk)

## Metallic & PTFE Assemblies – Standard End Configurations

Metallic and PTFE hose assemblies are available in a wide variety of end configurations in common materials including stainless steel, aluminium and mild steel.



Hoses Assemblies manufactured as an assembly to customer specification. Larger sizes available on request. All hoses are tested 150 p.s.i air under water and can be supplied with a wide range of certification if required.

All Hose Assemblies compliant with Pressure Equipment Directive 2014/68/EU

We reserve the right to change hose specifications without prior notice



Telephone: +44 (0)1772 323529

Email: [sales@dixoneurope.co.uk](mailto:sales@dixoneurope.co.uk)