



PA 440

Field Display for Current Loop with Contacts

Functional range

- ▶ free scalable display
- ▶ switch mode, hysteresis, parameterizable deceleration of the contacts
- ▶ no external power supply necessary

Product characteristics

- ▶ field display for pressure transmitter with output signal: 4 ... 20 mA / 2-wire or 0 ... 10 V / 3-wire
- ▶ 4-digit LCD display
- ▶ plastic housing
- ▶ pressure compensation element with PTFE-Filter

Optional versions

- ▶ IS-version
- ▶ 2 contacts
- ▶ 4-digit LED display

Typical application



in situ display at e.g. for tank batteries, pumping stations and much more



Analogue signal	
Standard	2-wire: 4 ... 20 mA
Option IS-version	2-wire: 4 ... 20 mA
Option 3-wire	0 ... 10 V (in preparation)
Accuracy	$\leq \pm 0.1\%$ FSO ± 1 digit
Supply	
2-wire system	supplied by current loop; voltage drop ≤ 6.5 V IS version: max. 28 V _{DC} (for combination with transmitter and PA 440)
3-wire system	display is supplied parallel with transmitter; V _S = 8 V _{DC} ... 36 V _{DC}
Contact	
Number, type	2 independent PNP open collector contacts
Switching performance	contact rating max. 125 mA, short-circuit resistant
Switching frequency	max. 8/sec
Delay time	0 ... 100 sec
Miscellaneous	
Electrical protection	reverse polarity protection (no damage, but also no function); electromagnetic compatibility (emission and immunity according to EN 61326); short-circuit protection
Ingress protection	IP 65
Display	4-digit, 7-segment LC display, range of indication -1999 ... +9999; accuracy 0.2 % ± 1 digit; standard: LC display, digit height 18 mm option: LED display, digit height 10 mm, red
Permissible temperatures	electronics / environment / storage: -20 ... 70 °C
Material display housing	plastic ABS, grey
Cable entries	cable gland M16x1.5 Polyamide, seals NBR, diameter range: standard 5 ... 10 mm
Atmospheric pressure compensation	pressure compensation element with PTFE filter
Terminal clamps	vertical clamps for stranded and solid wires up to 2.5 mm ²
Dimensions (height/width/depth)	80 mm x 120 mm x 57 mm
Weight	approx. 220 g
CE-conformity	EMC Directive: 2014/30/EU
Explosion protection (optionally)	
Approval AX15-PA 440	IBExU 08 ATEX1126 X / IECEx IBE 21.0023X zone 1: II 2G Ex ia IIB T4 Gb
Safety technical maximum values	U _i = 28 V _{DC} , I _i = 93 mA, P _i = 660 mW, C _i = 0 nF, L _i = 0 μ H
Ambient temperature range	from -20 °C to +70 °C
Wiring diagram	
Dimensions (in mm)	

© 2021 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

