


VC-80 I



Dimensions
DATA IN mm

A	266,6
B	172,6
C	72




CELY
VC SERIES



LCD
SEGMENT
DISPLAY



CONNECTABLE TO
PLATFORM UP TO
14 LOAD CELLS



INTERNAL
RECHARGEABLE
BATTERY



METROLOGICAL
VERIFICATION
OPTIONAL (EU)

Characteristics and functionality

Outstanding functions

- Weight-Tare-Accumulation.
- Checkweighing (minimum-maximum) with alarm.

Weighing

- Connection to weighing platform of up to 4 load cells.
- Up to 6,000 divisions. Monorange.

Construction

- Structure:
 - › Stainless steel.
- Keypad and display::
 - › Display with 7-keys and backlit LCD segment display of 3 digits (52 mm).

Power supply

- AC (12 V / 500 mA) adaptor.
- (6 V / 4 Ah) internal rechargeable battery.
 - › Up to 50 hours' runtime (depending on conditions of use).

Model

VC-80 I

Ref.: **71AVC80I00UE**

Options

Option	Specifications	Ref.
Metrological verification (M)	According to EU weighing directives for indicator + platform assemblies. (See section on equipment metrological verification).	Consult

Accessories



Stainless steel column kit

- H330 mm column
Ref: 494533B
- H660 mm column
Ref: 494535B