

# AIRPURION 90 active



The AIRPURION 48 active consists of a matt anodized and completely closed aluminium frame. Wiring system and the electronic cut-in unit are integrated into the frame.

Scope of delivery of an AIRPURION active plant also contains a mounting rack or a wire suspension for assembly.

applications	product line	AIRPURION 48 active
production or packaging of food	turnover of ambient air	36 m <sup>3</sup> /h
medical technology	disinfection 80%	approx. 550 m <sup>3</sup>
	disinfection 88%	approx. 75 m <sup>3</sup>
laboratories	weight	6,0 kg
preparation rooms in hotel kitchen	life time of lamps	10.000 h
	dimension (L x B x H in mm)	1000 x 105 x 105
	number of lamps	1
	protection grade	IP 54
	electrical connection	110-240 50/60 Hz
	total power	90 W
	over current protection	10 A

  

advantages
continuous operation, even if there are people staying in the room
not affecting smell or taste
low-maintenance operation
low operational costs



article number: 160 02200 0000

splinter protection  
wire suspension  
mounting rack



article number: 160 03900 0000

splinter protection  
wire suspension  
mounting rack



## equipment AIRPURION 90 active

PURION UV-lamp 90 W  
article number: 200 00600 0000



service-kit  
article number: 292 00900 0000

