


Name:

PolySeal Vario Twin

Description:

Semiautomatic foil application and sealing device for sealing of all sorts of plastic and glass containers



Equipment features

1. foil application device

PolySeal Vario DIS (left hand side)

- pneumatic drive stepless pressure regulation
- stepless manual height adjustment with height scale
- foil dispensing with 2 spot pre-sealing
- removable pre-sealing plates
- heat protection shield
- vacuum suction nozzle
- roller guide with running slide
- foil magazine for stackable pre-cut sealing lids
- VARIOTRONIC – control unit for the regulation of temperature, sealing time and pressure

2. sealing device

PolySeal Vario PN (right hand side)

- pneumatic drive
- stepless pressure regulation
- stepless manual height adjustment with height scale
- sealing head heating block, swingable, anodised aluminium
- hollowed out sealing die, adaptable to sealing head
- heat protection shield
- container holder
- VARIOTRONIC - control unit for the regulation of temperature, sealing time and pressure

Technische Daten

electrical power supply	230 V, 50/60 Hz	temperature setting	100-300 °C
sealing head heating block	100x100x25 mm	sealing time (cycle)	0.3-9.9 sec
pre-sealing heating block	30x100x30 mm	container size (height/outerØ/mouthØ)	max. 220/280/160 mm
nominal current	5 A	Festo ISO cylinder, sealing	D = 50 mm
power consumption, sealing	1 kW	cylinder stroke, sealing	25 mm
power consumption, foil application	0.5 kW	Festo ISO cylinder, foil application	D = 32 mm
compressed air (conditined)	1-5 bar	cylinder stroke, foil application	150 mm
air consumption	0.8 m ³ /h	weight	81 kg
sealing capacity	approx. 700 uph	dimensions (WxLxH)	700x620x740 mm
variable height adjustment	0-240 mm		

EC Declaration of Conformity in accordance with EC Directive (Machinery Directive) 2006/42/EC, Annex II 1 A is available.

Your sealing system from one source!

Aluminium seals from BALLERSTAEDT - suitable for your application.

Please contact us.

The information contained here is purely informative and non-binding.

Nr. 43943-E, Version: 3 - Datum/Ersteller: 14.07.2020/SL

Letzte Änderung: 22.01.2021/SL - Datum/Freigeber: 22.01.2021/HK

BALLERSTAEDT & CO. OHG

Hardbergstr. 11 • D-76437 Rastatt

www.ballerstaedt.de

Phone: +49 (0)7222/9515-0

E-Mail: sales@ballerstaedt.de