

Name: **PolyCos PN III**

Description: Semi-automatic sealing device for sealing plastic and glass containers



Equipment features


- pneumatic drive with high contact pressure (e.g. for glass sealing)
- infinitely variable height adjustment
- aluminium sealing head
- hollowed out sealing die, adaptable to sealing head
- container holder
- roller guide system
- digital control unit

Technical data

electrical power supply	230 V, 50/60 Hz
sealing head heating block	100x100x25 mm
nominal current	4 A
power consumption	1 kW
compressed air (conditioned)	1-5 bar
air consumption	2-5 m ³ /h
sealing capacity	approx. 600 uph
variable height adjustment	0-300 mm
temperature setting	100-300 °C
sealing time (cycle)	0.3-9.9 sec
container size (H/D)	max. 100 mm/200 mm
sealing stroke	25 mm
sealing power	max. 1.5 kN
weight	20 kg
dimensions (WxLxH)	300x480x500 mm



temperature control and height adjustment



jar in container holder on roller guide

EC Declaration of Conformity in accordance with EC Directive (Machinery Directive) 2006/42/EC, Annex II 1 A is available.

Your sealing system from one source!

Aluminium seals from BALLERSTAEDT - suitable for your application.

Please contact us.

The information contained here is purely informative and non-binding.

Nr. 45505-E, Version: 2 - Datum/Ersteller: 14.07.2020/SL

Letzte Änderung: 09.10.2020/SL - Datum/Freigeber: 09.10.2020/SL

BALLERSTAEDT & CO. OHG

Hardbergstr. 11 • D-76437 Rastatt

www.ballerstaedt.de

Phone: +49 (0)7222/9515-0

E-Mail: sales@ballerstaedt.de