PURION Pool 80



The integrated plant PURION PooL 80 consists of a filtration of sediments and UV based disinfection of pool water. It is applied to disinfect circulation water of pools.

The pre filter removes sediment from the pool water. The following UV based disinfection prevents biological activities – especially forming of algae.

applications	product line	PURION Pool 80
UV based disinfection of pool water up to 80 m ³	pool dimension	80 m^3 (20 h operation) 60 m^3 (15 h operation)
	dimension (L x B x H in mm)	850 x 630 x 1.290
	UV plant	PURION 2501
advantages	life time of lamps	10.000 h
plug and play system for immedi-	max. delivery rate rotary pump	12 m³/h
ate operation up to 95% reduction of chemicals compared to chemical treatment of the water	weight (without quartz granulate)	48 kg
	quantity quarztz	85 kg
considerable cost cutting due to	valve filter tank	top mount 4-Wege-Ventil
less cost for chemicals	protection grade	IP 54
low-maintenance operation	electrical connection	230 V
low operational costs	over current protection	10 A

1st step: filtration of sediments

The upstream filter unit with "top mount" 4-port valve consists of a polyethylene filter tank (filled with activated filter granulate - special quartz) and a rotary pump. This pre filter has two layers with different granulate

dimension that removes sediment from the pool water.

2nd step: disinfection with UV-light

The following UV based disinfection prevents biological activities – especially the formation of algae.

Unlike other cleaning procedures this approach does not produce potentially dangerous byproducts.

article-no.: 140 00500 0000 article-no.: 140 00600 0000



equipment PURION Pool 80

Quartz-granulate fine granularity article number: 292 02300 0000

Quartz-granulate coarse granularity article number: 292 02400 0000



stainless steel

.

PURION UV-lamp 90 W article number: 200 00600 0000

service-kit article number: 292 00900 0000

