

Circular Building Site Saw TZH 350 AVOLA Table Circular Saw TZV 315

TZH 350 with sawblade height adjustment and safety hood

TZV 315 with sawblade height adjustment and patented sawblade inclination 90° - 45°

For professional application! Against new standard EN 1870 - 1

Economical – Versatile – Strong – Accurate – Safety



Circular Saws

Standard Equipment

- Adjustable cross and rip cutting fences, hinged
- Undertable guideway, securely protected
- High quality TCT sawblade
- Machine frame completely galvanized, torsion – resistant
- Hinged table extension
- Powerful motors with extensive reserves of safety



TZH 350



TZV 315

Special Equipment

- Transport wheels for easy manoeuvrability
- Table width extension
- Dust extractor CF 4 – please ask for special brochure



Technical specification		TZH 350W	TZH 350	TZV 315W	TZV 315
Motor power input/output	kW	2,7/2,0	3,1/2,2	2,7/2,0	3,1/2,2
Three phase current	V		400 DS		400 DS
AC current	V	230 WS		230 WS	
Equipment plug		Schuko	CEE 516	Schuko	CEE 516
Sawblade speed	rpm	2710	2800	2710	2800
Sawblade TCT	mm	350/30	350/30	315/30	315/30
Cutting height 90°	mm	0–105	0–105	0–90	0–90
Table size L x W x H	mm	956/575/850	956/575/850	956/575/850	956/575/850
Weight	kg	83	83	77	77
Emission sound pressure run at load-no load	dB (A)	83,0/87,0	83,0/87,0	82,4/85,5	82,4/85,5

AVOLA MASCHINENFABRIK

A. Volkenborn GmbH & Co. KG
Heiskampstraße 11
D-45527 Hattingen
Postfach 80 02 28
D-45502 Hattingen
Telefon +49 / 23 24 - 96 36-0
Telefax +49 / 23 24 - 96 36-50
E-mail info@avola.de
www.avola.de