

Ball transfer units with countersunk housings

- KR-S = galvanized steel plate housing with steel ball
- KR-SVA = all parts from stainless steel
- KR-S-KU = galvanized housing with plastic ball
- Low installation height due to flange mounting
- with 2 or 3 mounting holes
- all load-carrying capacity specifications are valid for use with an upright ball
- the load capacity decreases for overhead installations



ball transfer series KR-S	dw mm	D mm	D1 mm	H mm	h mm	a mm	LK mm	B mm	load-carrying capacity kg
KR-S-15 Ident No.: 0028223	15.8	22.1	41.3	18.5	10.2	3.2	30	3.5	12
KR-S-20 Ident No.: 0014721	19	29.1	61	22	10	3.2	44.5	5.1	25
KR-S-25 Ident No.: 0014724	25	37.2	73	30	14.2	3.5	55.6	5.1	55
KR-S-30 Ident No.: 0014727	31.7	45.5	73.7	36.1	16.2	4.2	58.7	5.1	125
KR-S-40 Ident No.: 0014729	39.7	62	94.6	48.5	21.1	6.3	76.2	7	225
KR-S-50 Ident No.: 0014731	50.8	75.3	120.7	58.5	28.3	6.3	92	8	340
KR-SVA-20 Ident No.: 0014723	19	29.1	61	22	10	3.2	44.5	5.1	25
KR-SVA-25 Ident No.: 0014726	25.4	37.2	73	30	14.2	3.5	55.6	5.1	55
KR-SVA-30 Ident No.: 0014728	31.7	45.5	73.7	36.1	16.2	4.2	58.7	5.1	125
KR-SVA-40 Ident No.: 0014730	39.7	62	94.6	48.5	21.2	6.3	76.2	7	225
KR-SVA-50 Ident No.: 0014732	50.8	75.3	120.7	58.5	28.3	6.3	92	8	250

ball transfer series KR-S-KU	dw mm	D mm	D1 mm	H mm	h mm	a mm	LK mm	B mm	load-carrying capacity kg
KR-S-20-KU Ident No.: 0014722	19	29.1	61	22	10	3.2	44.5	5.1	20
KR-S-25-KU Ident No.: 0014725	25	37.2	73	30	14.2	3.5	55.6	5.1	24

