





Series OI

Reverse osmosis point of use (POU) water cooler.

With patented design reverse osmosis filtration integrated.

Superior quality, made entirely from stainless steel.



Model: M-77OI





Series OI

Integrated reverse osmosis system. Designed for the hardest water types.

The water cooler includes a high capacity filtration system that eliminates suspended solids and microorganisms to ensure the highest quality of pure water. It is recommended to use this filtration system in areas where the municipal water supply is of inferior quality and requires a higher capacity filter. Has the same features as model M77ID, but with an excess water drain from the osmosis filtering system.

Model

M-770I

- Cold water tap.
- Room temp. water tap.

INTEGRATED OSMOSIS SYSTEM IN M-770I

The compact design ensures reliable water flow avoiding the need for multiple connections or loss of water.


- Four Stage filtration with a pump Guarantees higher water quality.
- -High performance and high efficiency
 - High water production approx. 250l/day. High rate of input water use: 35%.

Technical data

Cooling Power (W)	205
Power consumption (W)	100
Voltage 230V 50Hz single-phase (A) (Consult other options)	0.5
Cooling capacity (Room temp.: 30°C, Input temp.: 27°C, Output temp.: 17°C) (I/h)	18
Cup filling time (sec.)	4
Cold water output temperature (regulated by thermostat) (°C)	4-11
Refrigerant gas (CFC-free)	R-134a
Dimensions (mm). Height x Diameter	1180 x 310
Net weight (kg)	19

HEADQUARTERS AND FACTORY Ronda de Llevant, 10 08820 El Prat de Llobregat Barcelona (Spain) T. +34 934 358 546 E +34 934 350 604

INTERNET www.canaletas.es www.canaletas.com infox@canaletas.es



Accessories

FILTERS

Reverse osmosis system made up of three filters and a reverse osmosis membrane, which must all be changed periodically.

CUP DISPENSER (optional) For easily accessible cups



220 cc capacity.

Series OI

